NASA TN D-1314

11

TECHNICAL NOTE

D-1314

BOILING HEAT TRANSFER TO LIQUID HYDROGEN AND NITROGEN IN FORCED FLOW

By James P. Lewis, Jack H. Goodykoontz, and John F. Kline

Lewis Research Center
Cleveland, Ohio

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

WASHINGTON

September 1962

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

TECHNICAL NOTE D-1314

BOILING HEAT TRANSFER TO LIQUID HYDROGEN AND NITROGEN IN FORCED FLOW

By James P. Lewis, Jack H. Goodykoontz, and John F. Kline

SUMMARY

Boiling heat transfer to liquid hydrogen and nitrogen was investigated experimentally. Results are presented from a study of bulk boiling inside a cylindrical tube under vertically upward forced-flow conditions. A 0.555-inch-inside-diameter and $16\frac{1}{8}$-inch-long electrically heated stainless-steel tube was used. The range of variables studied for hydrogen were mass velocity of 2850 to 17,000 pounds per hour per square foot, local heat flux of 3600 to 40,000 Btu per hour per square foot, inlet pressure of 30 to 74 pounds per square inch absolute, and inlet subcooling of 0° to 9° R. Nitrogen test conditions were mass velocity of 15,000 to 56,000 pounds per hour per square foot, local heat flux of 2300 to 40,000 Btu per hour per square foot, inlet pressure of 47 to 56 pounds per square inch absolute, and inlet subcooling of 1° to 6° R.

The axial distribution of the tube-wall temperatures is presented. A transition in the type of boiling heat transfer was obtained. The critical heat flux corresponding to this transition was determined over a range of flow and heating rates and local qualities. At specific combinations of flow and transition location, a range of critical-heat-flux values was obtained and maximum values were determined. The maximum critical heat flux increased with increasing fluid-flow rate and decreased with increasing length of tube before transition. Similar variations of the maximum critical heat flux have been reported for water. The tube-inner-wall temperatures upstream of transition were essentially uniform and were only slightly greater than the fluid saturation temperature. The wall-temperature profiles downstream of transition generally resembled those obtained in film-boiling studies and appeared to be strongly dependent upon local quality at the point of transition. Maximum wall temperatures of 900° and 1800° R were obtained with hydrogen and nitrogen, respectively. Fluctuations of pressure, flow rate, and temperature occurred during some of the boiling tests. Under some conditions, maximum critical-heat-flux values were attained during steady-state operation with fluctuations. In other cases the fluctuations became uncontrolled, and critical-flux values less than the maximum values were obtained upon restabilization of the test conditions. No measurable pressure drop across the test section was obtained at any condition.

INTRODUCTION

Liquid hydrogen has been proposed for use in several advanced propulsion systems. In these systems, hydrogen may be used both as a propellant and as a coolant. The low boiling point of hydrogen and the desirability of storing it in the liquid state in addition to the requirements of some systems for gaseous hydrogen necessitate a knowledge of two-phase flow and heat transfer for hydrogen. Information is especially desired for boiling heat transfer of hydrogen under forced-flow, confined-geometry conditions. In addition, the wide variance of the physical properties of hydrogen from those of more conventional fluids make it attractive as a test fluid in research directed towards a more complete understanding of the general problem of boiling heat transfer.

Information in the literature concerning boiling heat transfer, primarily for the case of pool (or pot) boiling and usually for conventional fluids, such as water and alcohols, is extensive. Present thinking with respect to pool boiling and related investigations with hydrogen are summarized in reference 1. Pool boiling is characterized by three distinct modes of boiling, namely, nucleate, transition, and film boiling. Analytical and empirical relations between the heat flux (or heat-transfer coefficient) and the wall- to fluid-temperature difference have been obtained for pool boiling. Pool boiling also exhibits a distinctive value of heat flux obtained at the boundary between the nucleate and transition boiling regions that has been variously termed maximum nucleate flux, departure from nucleate boiling (DNB), or burnout heat flux. Analytical and experimental correlations of the maximum nucleate flux with fluid properties and test operating variables have been made with varying degrees of success (ref. 1).

For the case of forced flow in confined geometries, the current understanding of boiling heat transfer is much more limited, especially for the case of net vapor generation. Again, considerable data have been obtained and several correlations have been proposed (refs. 2 to 6). Much of the available data are incompletely presented or contradictory, and the correlations, which successfully relate the results of a single study, have not been successful when applied to other tests or fluids of widely differing properties. The experimental data of several investigations (refs. 2 to 4) have indicated the existence of a critical heat flux, which somewhat resembles the maximum nucleate flux obtained in pool boiling, in that a well defined reduction in the heat-transfer coefficient is obtained. Some data of this type that resemble the usual results obtained for pool boiling were obtained in limited tests of boiling hydrogen (ref. 7). Data were obtained in reference 8 for hydrogen for the region that might be termed film boiling in tubes with forced flow. For the investigations of boiling heat transfer with forced flow in confined geometries, there is a wide variation in the assumptions regarding the physical nature of the heat-transfer process and in the definition of the critical heat flux.

Because of the aforementioned limitations of present knowledge, a program was initiated at the Lewis Research Center to investigate boiling heat transfer to liquid hydrogen under conditions of forced flow inside a vertical tube. The principal objective of the investigation was to determine in engineering terms the effect of the operating variables (flow rate, pressure, liquid inlet subcooling, heating rate, and tube geometry) on the mode of heat transfer and their relation to the value of the critical heat flux. The program was directed towards conditions resulting in net vapor generation. In addition, information on flow instability and its effect on heat transfer were desired.

The test apparatus consisted of a pressure-fed, once-through system with an electrically heated vertical tube of 0.555-inch inside diameter and $16\frac{1}{8}$-inch length. Both subcooled liquid para-hydrogen and liquid nitrogen flowed through the tube in vertical upflow. The range of variables investigated was limited to the following:

	Hydrogen	Nitrogen
Mass velocity, lb/(hr)(sq ft)	2850 to 17,000	15,000 to 56,000
Local heat flux, Btu/(hr)(sq ft)	3600 to 40,000	2300 to 40,000
Liquid inlet subcooling, ^{o}R	0 to 9	1 to 6
Inlet pressure, lb/sq in. abs	30 to 74	47 to 56

Tube-exit qualities ranged from essentially 0 to 1.0 (with superheat), and transition from a relatively high to a lower value of heat-transfer coefficient occurred over a range of axial locations from tube entrance to exit. A few tests were made with cold hydrogen gas flowing through a heated tube. The results obtained from the investigation are presented in tabular and graphical form.

APPARATUS

General Arrangement

The test equipment included a liquid-supply Dewar, a controlled source of pressurizing gas, a flash cooler to subcool inlet test liquid, the test section and electric power supply, inlet and exit control valves, a vaporizer, an orifice-type flowmeter, and vent, pressure relief, and purge systems (fig. 1). In practically every case, the test liquids (para-hydrogen and nitrogen) were pressurized by their own gases. Gaseous helium was used for system purging and inerting. The vaporizer was used to ensure that only a fully vaporized product would pass through the flow orifice. All fluid lines from the supply Dewar to a point past the end of the test section were insulated with a vacuum jacket.

Test Section

The test-section assembly consisted of the electrically heated tube, inlet and outlet chambers, a vacuum jacket, and test instrumentation (fig. 2). The tube was made of type 304 stainless steel with a 0.555-inch inside diameter and a 0.035-inch-thick wall. As indicated in figure 2, the effective heated length of the tube was $16\frac{1}{8}$ inches, measured between the inner faces of the end flanges. All distances along the tube from the tube inlet were measured from the downstream side of the inlet flange. The actual inlet end of the tube extended 1/2 inch upstream of this point. The inlet chamber consisted of a $1\frac{1}{2}$-inch-inside-diameter stainless-steel cylinder attached to the inlet flange. The inlet chamber, which was lined with 1/8-inch-thick thermal insulation, was designed to provide a low-velocity plenum at the test-section entrance and to minimize heat leakage from the heated test section to the incoming liquid. Two copper bus bars, diametrically opposite, were connected between the test-section inlet flange and the bottom flange of the vacuum jacket, which also served as the ground side of the electrical circuit. These bus bars were 4 inches long with a cross section of 1/8 by 1 inch. The outlet chamber was designed to minimize heat losses from the tube, to provide an electrically insulated, low-electrical-resistance connection to the tube, and to provide a thermally insulated mixing chamber, in which the test fluid could come into thermal and phase equilibrium. The outlet chamber contained an inner liner consisting of stainless steel and Teflon. This liner, which was not attached directly to the tube, was designed to allow cool gas to accumulate between it and the outer shell and thus to act as thermal insulation. The outlet section was connected to a 1-inch-outside-diameter copper tube that passed through the vacuum jacket and was electrically isolated from it. Two conically shaped mixing screens were placed in the outlet section. The vacuum jacket around the test-section assembly consisted of stainless-steel flanges with O-ring seals, a $3\frac{1}{2}$-inch-diameter Lucite tube, and an aluminum-foil radiation shield.

Flash Cooler

The flash cooler shown in figure 1 was provided to supply subcooled liquid to the test section. The cooler consisted basically of three concentric tubes. The flow of the liquid to the test section was brought through the small innermost tube. Some liquid was allowed to pass into the annular space around the inner tube through bleed holes at various points along the length of the subcooler. The pressure in this annulus was maintained intermediate between atmospheric pressure and the supply Dewar pressure by a throttle valve. The liquid entering the annular

space vaporized because of the drop in pressure and thus cooled the inner supply tube. The inner tube had a 0.38-inch outside diameter with a 0.032-inch wall. Stainless-steel rods, 1/4 inch in diameter, were inserted into the inner tube to promote cooling of the supply liquid. The outer annular space provided a vacuum jacket for thermal insulation.

Electric Power Supply

The tube was heated by alternating current supplied through a $2\frac{1}{2}$-kilowatt, 60-cycle transformer with a maximum current rating of 500 amperes. The power to the test section was controlled by a variable autotransformer in the primary circuit. The current to the test section was measured by a laboratory-quality ammeter connected to a current transformer with a ratio of 100. Voltage drops across the tube at various locations were measured with a Ballantine vacuum-tube voltmeter.

Instrumentation

Instrumentation was provided to measure the inlet and the exit fluid bulk temperatures, the tube-wall temperatures, the inlet-fluid pressure, and the test-fluid flow rate.

Fluid temperatures. - The fluid bulk temperatures were measured by carbon resistors in the inlet and the exit of the test section (see fig. 2). The carbon resistors at the test-section outlet were located both above and below the mixing screens. The carbon resistors were hermetically sealed in a protective sheath about 0.1 inch in diameter by 0.2 inch long. The carbon resistors acted as one arm of a bridge circuit, the output of which was recorded on a self-balancing potentiometer. The slope of the temperature-resistance curve was obtained in a laboratory calibration and was essentially invariant. Shifts of the curve occurred, however, that required daily adjustment with a trimming resistance at a known temperature condition. The fluid temperature at the orifice flowmeter was measured with a copper-constantan thermocouple. The overall accuracy of the fluid bulk temperatures is estimated at approximately $\pm 0.5^{\circ}$ R.

Wall temperatures. - The temperatures of the tube wall and of adjacent sections were obtained with copper-constantan thermocouples. The thermocouples were soldered to the outside of the tube wall and the leads were wrapped around the tube several times and were finally wrapped with glass-fiber tape. The tube-wall thermocouples were positioned in one longitudinal plane and their axial locations are given in table I. The positions of the thermocouples that were installed on the inlet section, the outlet section, and the ground bus are also given in table I. These thermocouples were used to monitor the flow of heat to and from the test section.

The constantan wire from each thermocouple junction was led without interruption to individual reference junctions located in a liquid-nitrogen bath at atmospheric pressure. Copper leads led from the bath to a manual selector switch. The thermocouple voltage was bucked by a 1-millivolt voltage to obtain positive values, and the resultant signal was recorded on a self-balancing potentiometer. The calibration of the thermocouples was determined from the National Bureau of Standards calibration (ref. 9) and laboratory calibration checks. The calibration indicated a very low sensitivity for the copper-constantan thermocouples near liquid-hydrogen temperatures. Wall temperatures, however, were obtained from approximately 40° to 1800° R. Above 1200° R, an extrapolation of the curve of reference 9 was used. The sensitivity and accuracy of the thermocouple readings are indicated by the following table:

	Liquid-hydrogen temperature (45° R)	Liquid-nitrogen temperature (160° R)	Room temperature (530° R)
Sensitivity, mv/°R	0.004	0.01	0.022
Chart reading limit, mv	0.01 to 0.02	0.01 to 0.02	0.01 to 0.02
Chart reading limit, °R	2.5 to 5	1 to 2	0.5 to 1

The thermocouple calibration points also showed a scatter of approximately ±3° R at liquid-hydrogen temperatures and ±1° R at liquid-nitrogen temperatures. Approximately the same scatter was obtained from the actual tube-wall thermocouples during no-heat runs. The tube-wall thermocouples were attached to the outside of the tube wall. The temperature of interest, however, is that of the inner surface. An analysis and computation of the temperature drop through the tube wall is given in appendix A for the case of negligible axial temperature gradients. This analysis indicates wall drops of up to 20° R for liquid-hydrogen conditions and up to 7° R for liquid-nitrogen conditions over the range of the test heat fluxes.

Pressure. - The fluid pressures were sensed with strain-gage-type transducers and were continuously recorded on a high-speed recording potentiometer (0.3-sec full-scale travel). Pressure was sensed at the test-section inlet (see fig. 2) by a transducer having a range of 0 to 100 pounds per square inch absolute and an overall accuracy of ±0.5 percent of full scale. Initially a differential pressure transducer was installed to measure the pressure drop across the test section. Since no measurable pressure drop was obtained at the largest flow and vaporization conditions, the downstream pressure tap was removed to aid in eliminating flow and pressure oscillations. The fluid pressure far downstream of the tube exit (upstream of the exit control valve) was monitored on a visual gage but showed no significant drop from the test-section inlet pressure. The pressure in the flash cooler was also sensed by a strain-gage transducer.

Flow rate. - The test-fluid flow rate was measured by a sharp-edge orifice downstream of the vaporizer. The vaporizer ensured that all the fluid was in the gaseous phase and at a temperature at which fluid properties are well known. The discharge coefficient was determined with water for a range of Reynolds numbers. The orifice pressure and pressure drop were measured with strain-gage-type transducers and recorded on a self-balancing potentiometer. The flow-rate measurements are estimated to have an accuracy of ±2 percent.

PROCEDURE

Establishment of Test Conditions

Obtaining information on boiling heat transfer for various heating rates at several pressure levels and over a range of flow rates in a systematic way was desired in order that the effects of each variable could be determined. It was also desired to have the test liquid enter the test section slightly subcooled and to study heat transfer and two-phase flow in forced flow over as great a range of fluid quality as possible and to obtain a critical heat flux at arbitrary locations along the tube axis. (The critical heat flux is defined as the flux immediately before the transition from the high upstream heat-transfer coefficient to a lower value.) Completely systematic operation was not always possible because of limitations of the test equipment and of the boiling process itself. In addition, operation at a precise preselected condition was difficult to attain because of fluctuations of flow and pressure that occurred in the system.

The general operating procedure consisted of setting conditions of flow rate, pressure, and inlet subcooling without heat addition and then gradually increasing the heat to the test section in small increments until the desired condition was obtained. As heat was added to the system, the flow and pressure conditions changed and had to be continually readjusted. The most consistent and repeatable results were obtained by always increasing the heat control setting and/or decreasing the flow rate. The range of test variables for the investigation of boiling heat transfer were test-section pressure, 30 to 74 pounds per square inch absolute; mass velocity, 2850 to 17,000 pounds per hour per square foot for hydrogen and 15,000 to 56,000 pounds per hour per square foot for nitrogen; inlet subcooling of 0° to 9° R for hydrogen and 1° to 6° R for nitrogen. The heated-tube-wall temperatures varied from 36° to 1800° R. The point of transition from a high to a lower heat-transfer coefficient was obtained at various locations along the length of the tube. Occasional unheated runs were made before and after a heated run. For an unheated run made after a heated condition, the flow and pressure controls were left unchanged in order that the effect of boiling on the flow conditions might be studied. A few runs were made in which cool hydrogen gas flowed through the tube at nominal pressures of 50 and 70 pounds per square inch absolute, inlet temperatures of 46°

to 82° R, and mass velocities of 7800 to 13,000 pounds per hour per square foot.

Data Reduction and Computations

All wall temperatures were obtained from the thermocouple chart readings and the aforementioned copper-constantan thermocouple calibration. Inner-tube-wall temperatures for a negligible axial temperature gradient were obtained from the calculations of appendix A. All pressures were read directly from the recorder charts. The flow rate was computed by the standard ASME orifice equations. Fluid properties were taken primarily from National Bureau of Standards sources (refs. 9 and 10).

The local heat flux was computed from the measured current and tube-outer-wall temperature by equation (A11).

The local vapor quality was obtained from a heat balance by the relation

$$x = \frac{Q - wc_p(t_{sat} - t_{in})}{wh_{fg}} \tag{1}$$

(All symbols are defined in appendix B.) For the special case of negligible axial temperature gradient (hence, constant heat flux), the quality is given by

$$x = \frac{4\left(\frac{q}{G}\right)\left(\frac{L}{D}\right) - c_p(t_{sat} - t_{in})}{h_{fg}} \tag{2}$$

Heat balances were computed for a few cases by comparing the enthalpy rise of the fluid through the test section with the amount of electric heat supplied to the test section. The heat balance could be computed only for cases with subcooled inlet liquid and superheated exit vapor (except for the hydrogen-gas runs) because there was no independent means of measuring quality. The heat balances agreed in most cases within ±10 percent. Usually the heat input was greater than the measured increase in fluid enthalpy, which indicated a heat loss. The main sources of heat loss (or gain) are the vacuum jacket, the copper ground bus, and the inlet and the exit sections. Calculations indicated that heat transfer across the vacuum jacket to the test section was negligible. Conduction through the copper ground bus was into the inlet section and was less than 5 percent of the heat generated in the tube. The heat loss from the tube through the walls of the inlet section was less than 2 percent of the heat generated in the tube. Evaluation of the heat loss at the exit of the test section was impossible. An additional source of error arose from the possible nonequilibrium of temperature and the phase of the test

fluid at the points of measurement in the inlet and the exit sections. The heat balance, however, was satisfactory and within the accuracy expected from the individual measurements.

RESULTS AND DISCUSSION

Tabulation of Data

The data obtained in 160 separate runs are tabulated in table II. Included in the table are data for runs both with liquid hydrogen and with liquid nitrogen, both heated and unheated, and also heated and unheated gaseous-hydrogen runs. The original data consisted primarily of the tube-outer-wall temperatures and the fluid exit bulk temperature obtained for various tests conditions of pressure, inlet fluid temperature, flow rate, and heating rate. For cases in which significant fluctuations of tube-wall temperatures occurred, the magnitudes of such fluctuations are also tabulated. The runs are numbered in chronological order. An omission in the run-number sequence indicates an aborted run or a significant change in the testing program. Also presented in table II are the temperatures measured on the electrical ground bus and in the inlet and the outlet sections. The table also contains the calculated values of the fluid inlet subcooling, the fluid exit superheat, the critical heat flux (or the uniform flux on the tube if it is below the critical value), the position of the point of transition in heat transfer (termed the critical-boiling-length-to-diameter ratio), and the local quality at the point of transition (termed the critical quality). The remarks tabulated for each run are based on observations made during the test and also on subsequent study of the data.

Tube-Wall Axial-Temperature Profiles

The tube-outer-wall temperature profiles along the length of the tube for liquid-hydrogen tests at a pressure of approximately 50 pounds per square inch absolute and an average inlet subcooling of 2° R are presented in figure 3 for various heating rates at two different nominal mass velocities. Also included in the figure are the temperatures of the inlet and the outlet sections and a schematic diagram of the test-section geometry, including thermocouple locations. All the profiles of figure 3 have the same general shape but show trends with respect to heating rate and mass velocity. Starting at the tube inlet, the wall temperatures are essentially constant until a sudden temperature rise is obtained at various downstream locations. Following the initial sharp rise, the slope of the temperature profile decreases and in some cases the curves appear to approach a constant temperature. Listed in figure 3 are the values of the local heat flux existing immediately upstream of the

point of temperature rise. This heat flux, arbitrarily termed the critical heat flux, is indicative of a boiling heat-transfer condition at which, for a given flow and pressure, a transition occurs from a relatively large heat-transfer coefficient to a smaller coefficient at a specified position along the tube axis. (The flux downstream of the transition point is larger than the critical flux because of the increase in tube electrical resistance, but the proportionate increase in flux is much less than the increase in wall temperature.) The critical flux may not correspond to the maximum nucleate or burnout flux obtained in pool boiling; for the terms to be synonymous, evidence would be required that the critical heat flux results from surface ebullition.

All the data of figure 3 show an increase in the critical heat flux as the location of transition moves upstream. This inverse relation was also found in tests with water for transition occurring at the exits of tubes of various lengths (ref. 4). The temperature-rise curves for the nominal mass velocity of 12,000 pounds per hour per square foot (fig. 3(a)) show a more pronounced change in slope and tend to approach a constant value of temperature sooner than those for the lower flow rate (fig. 3(b)). These effects are probably related to the lower qualities at the critical point obtained at the higher flow rate; however, a difference in the two-phase flow pattern (void-fraction distribution) is felt to be the controlling factor.

All the wall temperatures of figure 3 upstream of transition are uniform along the tube within the limits of the instrumentation and show a small and nonsystematic variation between runs. The inner-wall temperatures can be obtained by subtracting the wall-temperature drop (given in appendix A) from the outer-wall temperatures of figure 3. The inner-wall temperatures are approximately 12° and 3° R above the inlet fluid saturation temperature for the conditions of figures 3(a) and (b), respectively. These small temperature differences are not considered accurate enough for further analysis because of the inherent inaccuracy and lack of sensitivity of the temperature measurements at these low temperatures (40° to 70° R).

Since the highest wall temperatures obtained with hydrogen never exceeded 900° R and in most cases were less than 600° R, safe operation over a considerable range of conditions in a region equivalent to film boiling with forced flow seemed possible. Similar magnitudes of wall temperature were obtained in reference 8.

The tube-wall temperature profiles obtained with liquid nitrogen as the test fluid were generally similar to the results with hydrogen. (All nitrogen data are given in table II(b).) The rise in wall temperature following transition was much steeper for nitrogen than for hydrogen and the high temperatures (up to 1800° R) obtained finally caused failure of the test apparatus. During operation with liquid nitrogen,

attempts to obtain transition upstream of the tube exit generally resulted in unstable conditions with extreme fluctuations of flow, pressure, and wall temperature.

A few tests were made in which cool hydrogen gas flowed through the heated tube. These tests were made to obtain tube-wall axial temperature profiles for conditions of gas convective heat transfer for comparison with the temperature profiles obtained with boiling heat transfer. The profiles shown in figure 4 are for turbulent convective heat transfer and are considerably different from those obtained with boiling heat transfer (fig. 3). For the convective heat transfer, the tube-wall rise always started close to the tube inlet and the wall-temperature rise was generally more gradual than for the boiling heat-transfer tests. The shape of the convective wall-temperature profiles results primarily from entrance effects and variations in the tube-wall- to fluid-bulk-temperature ratio. The shape of the wall-temperature profiles for the boiling case (fig. 3), however, reflects changes in phase and in the boiling heat-transfer mechanism.

Temperature profiles are presented in figure 5 for boiling hydrogen at two constant values of transition location for several values of mass velocity and critical heat flux. An increase in mass velocity tends to skew the temperature-rise curves by increasing the slope at first and then by decreasing it at downstream locations. This effect of mass velocity on the temperature-rise curves was previously shown by the data of figure 3.

Critical Heat Flux

The critical heat flux for the conditions of this investigation corresponds to the local heat flux just upstream of the location of a sudden rise in wall temperature. For the critical heat flux at the end of the tube, transition was defined as the point corresponding to the conditions existing just previous to the increase in flux that first caused the thermocouple located 1/2 inch from the tube exit to rise. The critical heat flux obtained for boiling liquid hydrogen at a pressure of approximately 50 pounds per square inch absolute is presented in figure 6 as a function of mass velocity for four nominal values of the critical-boiling-length-to-diameter ratio L/D. All these curves show a significant increase in the critical flux with increasing mass velocity, but the slope of the curves generally decreases with increasing mass velocity. Generally the critical flux increases as the L/D decreases for constant mass velocity. Similar relations were found for water in reference 4, in which transition occurred at the exit of tubes of various lengths and diameters. In the present investigation, the length variation was obtained by causing transition to occur at various locations along a tube of constant length and diameter. The data of figure 6 show

an increased scatter with reduction in the critical L/D. The points of greatest heat flux in figure 6(d) also had the greatest fluctuations of wall temperature, flow rate, and pressure but were essentially steady-state conditions. The points along the lower envelope of critical flux in figure 6(d) did not show any fluctuation. Some of these lower points were obtained by deliberately overheating and then decreasing power and/or by increasing the flow rate until a stable condition was obtained. The rest of the lower points were obtained by a similar, but uncontrolled, process that could occur independently following a perturbation and that would eventually result in a stable condition. The highest flux values obtained at a given operating condition are arbitrarily termed the maximum critical heat fluxes. Throughout the investigation the maximum critical heat fluxes were generally associated with fluctuations of wall temperature, flow rate, and pressure, while the lower values of critical flux normally occurred without fluctuations. The scatter of the critical-flux values increased as the transition point moved upstream for the entire investigation with both liquid hydrogen and liquid nitrogen. The temperature profiles presented in figures 3 and 5 are from tests in which the maximum critical flux was obtained.

The temperature profile for a maximum-critical-heat-flux case is compared with the temperature profile obtained at a lower value of critical flux in figure 7. All other conditions of flow rate, pressure, and inlet subcooling are essentially the same. The main difference in the two profiles is a higher temperature level for the maximum critical flux case, which reflects the increased heating rate. The lower critical flux was obtained by deliberately overheating and then by cooling.

Tube-wall-temperature profiles for tests with critical heat fluxes less than the maximum are presented in figure 8 for an essentially constant mass velocity and various transition locations. For transition occurring at a value of L/D of less than 8 (axial distance L of about 4), the profiles each have a definite peak and a minimum as contrasted with the profiles for larger values of L/D and the profiles of figures 3 and 5.

Some runs were made with the wall-temperature rise occurring at or near the tube inlet. The resulting profiles are shown in figure 9 for two pressures and various mass velocities. Many of these curves have peaks and minimum points and in this respect are similar both to the profiles of figure 8 for values of L/D of less than 8 and to the profiles reported in reference 8. The shape of the curves of reference 8 was explained on the basis of an inlet end effect, a two-phase annular-flow model with the associated momentum pressure drop along the tube, and the attainment of "dry-wall" or "vapor-binding" conditions. In the tests presented herein, no measurable pressure drop across the test section was obtained, but dry-wall conditions could be attained. The data of figure 9 do not seem to indicate any significant effect on the critical

heat flux of the increase in pressure from 50 to 70 pounds per square inch absolute. Whether the critical-heat-flux values for the data of figure 9 should be classified as maximum or submaximum values is not known. Additional data for small values of transition length are necessary to resolve this question.

The critical-heat-flux data for hydrogen that are considered to be maximums are shown in figure 10 in logarithmic coordinates as functions of mass velocity for several critical L/D's. Lines of constant quality of 1.00 and 0.50 computed from a heat balance are also indicated in figure 10. The general trend of the data is similar to that obtained for the boiling of water at low pressure (ref. 4). The water data indicated a change of slope or a knee in the curve of flux against mass velocity with the knee at a quality of approximately 0.50. The hydrogen data, however, do not exhibit any marked change in slope, particularly in the region of a quality of 0.50. The hydrogen data are fairly limited compared with the water data of reference 4. The hydrogen data can be extrapolated to higher and lower qualities in a manner which would show that a knee occurs in the quality range of 0.60 to 0.70. These same data are cross plotted against the critical-length-to-diameter ratio in figure 11, which shows the inverse relation between the critical heat flux and the critical L/D. This effect is greatest for high qualities. Extrapolating the curves to small critical values of L/D would indicate a small effect of L/D on the maximum critical flux. This condition makes it difficult to determine if the data shown in figure 9 represent maximum-critical-flux values.

The variation of the critical heat flux with mass velocity for boiling liquid nitrogen is presented in figure 12. The results are given for transition at the end of the tube only (L/D = 29). For smaller values of critical L/D, the critical heat fluxes that were obtained were less than those of figure 12 at corresponding operating conditions. For this reason, the critical fluxes obtained upstream in the tube with nitrogen are not regarded as maximum critical fluxes as defined herein. Attainment of such maximum critical fluxes at critical values of L/D of less than 29 would be difficult and would require an improved apparatus with respect to stability control and material temperature limits. The general trend of the data of figure 12 agrees with that for hydrogen at a similar critical value of L/D (fig. 10) but with the critical flux at a larger value of mass velocity at approximately the same quality. This result reflects the lower latent heat of vaporization of nitrogen compared with hydrogen.

The data of figure 12 are also plotted in figure 13 together with the critical-flux data obtained with critical values of L/D of less than 29. The dashed line in figure 13 represents a quality of 1.00 for L/D of 29. With the exception of one point, all the critical-flux data for the short L/D tests fall below that for L/D of 29. In addition,

the critical flux obtained upstream of the tube exit appears to be independent of the location of transition over a considerable range of L/D. The resemblance between figure 13 of this report and figure 4 of reference 4 should be noted. Figure 4 of the reference for water (ref. 4) showed that the presence of compressible volumes limited the stability of the system and caused low values of critical flux. A similar, though unknown, limitation of system stability apparently existed for the nitrogen tests with transition upstream of the tube exit.

Normalization of Critical-Heat-Flux Data

Previous investigators (refs. 2 to 4) have tried various means of correlating and normalizing critical-heat-flux results. These efforts have been primarily empirical approaches. In reference 4, a large amount of data was normalized for forced-flow boiling of low-pressure water by using parameters including tube diameter, tube length, and mass velocity. The maximum-critical-heat-flux data of the present investigation are presented in terms of the parameters of reference 4 in figure 14 and compared with the water data of reference 4. The cryogenic data appear to be successfully normalized into single curves for each fluid with an acceptable degree of scatter. The normalized curves for the three fluids have the same general trends and are separated in the order of their respective latent heats of vaporization. A similar normalization of the data is shown in figure 15 but with slightly different powers of the length and the diameter terms. The normalization of the data in figure 15 appears to be equally as good as that in figure 14. Selection of the correct correlating parameters seems difficult without a realistic model of the two-phase flow and heat transfer, particularly for the cases of qualities approaching 0 and 1.00.

Acceptance of the normalization of the critical-heat-flux data in the form of figures 14 and 15 would imply an effect of the critical boiling length on the critical heat flux in addition to that required by a heat balance. If the length term is assumed to have no other effect than that required by a heat balance, the critical-flux data should be normalized by a plot of the critical flux against the mass velocity divided by the critical-length-to-diameter ratio L/D; that is, the critical heat flux is a unique function of the local critical quality for a given fluid. The hydrogen maximum-critical-heat-flux data is shown in this way in figure 16. The dashed line represents a quality of 1.00 for all length values. The scatter of the data in figure 16 is only slightly worse than in figures 14 and 15. The actual data scatter appears to be unsystematic with the possible exception of the smallest L/D conditions, for which the heat-flux values fall lower than the rest of the data. Similar trends were obtained with the water data of reference 4; that is, the fluxes for small L/D data were low. The failure of the small L/D data to correlate with the rest of the results in a graph such as

figure 16 may be attributed to several factors, in addition to questions concerning the validity of the choice of correlating parameters. These are: (1) The data at small critical values of L/D were the most difficult to obtain and had the greatest tendency towards instability; (2) at short lengths, heat transfer and two-phase flow equilibrium may not have been achieved; and (3) the data at small values of L/D may be reflecting entrance effects. The relation between the maximum critical heat flux and the critical length has therefore apparently not been completely determined. An additional complicating factor is involved in the selection of the correct critical length. The water tests of reference 4 had considerable inlet subcooling and would be expected to have an appreciable length of subcooled boiling, whereas, in the present investigation, the subcooling was negligible and bulk boiling occurred over nearly the entire length. Whether the effective length should be measured from the tube inlet or from the location at which the fluid bulk reaches the local saturation temperature is unknown. This problem is treated in reference 3 in a discussion of the use of quality as a correlating parameter for the critical heat flux.

Wall Superheat

A conventional method of presenting boiling heat-transfer data (especially for pool or pot boiling) is a graph of the heat flux against the wall superheat (wall temperature minus the fluid saturation temperature). Data for nitrogen are presented in this form in figure 17. These data include both the maximum-critical-heat-flux conditions and conditions below critical (no transition). Most of the data appear to fall on a single curve with no significant effect of mass velocity. Included in figure 17 are the predictions of reference 11 for nitrogen and of reference 5 for nitrogen and water. It is claimed in reference 5 that the method presented therein of predicting boiling heat fluxes applies to flowing systems as well as to nucleate pool boiling. The results shown in figure 17 should not be interpreted as supporting the analytical predictions or their application to flowing systems. The agreement may be fortuitous, especially because of the limited extent and accuracy of the nitrogen data. Similar graphs for the hydrogen data are not presented because of the poor sensitivity of the copper-constantan thermocouples at hydrogen temperatures. In fact, the sensitivity of the thermocouples for the nitrogen conditions is considered marginal. Analytical predictions indicate a wall superheat of 1° to 3° R for the range of the hydrogen test conditions. The experimental data show a wall superheat of the order of 10° R or greater. Attributing this lack of agreement entirely to limitations of the thermocouples appears difficult. The data of reference 7 for hydrogen do not fully correlate with the analytical predictions of references 5 and 11.

SUMMARY OF RESULTS

The results of the investigation of boiling heat transfer to liquid hydrogen and nitrogen in forced flow may be summarized as follows:

1. Boiling heat-transfer data (wall temperatures and heat fluxes) were obtained for bulk boiling of liquid hydrogen and nitrogen under forced flow upward inside an electrically heated tube. Data were obtained over ranges of flow and heating rates and pressures for small amounts of inlet subcooling. A limited amount of data was obtained with flowing cool hydrogen gas.

2. A transition in the type of boiling heat transfer was obtained. The critical heat flux corresponding to this transition was determined over a range of flow and heating rates and qualities. At specific combinations of flow and transition location, a range of critical-flux values was obtained and maximum values were determined. The maximum critical boiling heat flux increased with increasing fluid-flow rate and decreased with increasing length of tube before transition. The variation of the maximum critical flux with flow rate and critical boiling length was similar to that previously obtained with water.

3. Tube-inner-wall temperatures upstream of transition were essentially uniform and were only slightly greater (less than 20° R) than the fluid saturation temperature. Wall temperatures downstream of transition were considerably greater and the wall-temperature profiles generally resembled those obtained in film-boiling studies. The form of the wall-temperature rise downstream of transition appeared to be strongly dependent on the fluid quality at the point of transition. Maximum wall temperatures of 900° and 1800° R were obtained with hydrogen and nitrogen, respectively.

4. Fluctuations of pressure, flow rate, and temperature occurred during some of the boiling tests. Under some conditions, maximum critical-heat-flux values were attained during stable operation with fluctuations. In other cases the fluctuations became uncontrolled, and restabilization of the test condition resulted in critical-flux values less than the maximum values.

5. No measurable pressure drop across the test section was obtained at any condition.

Lewis Research Center
National Aeronautics and Space Administration
Cleveland, Ohio, May 29, 1962

APPENDIX A

COMPUTATIONS AND DATA REDUCTION

Temperature Drop Across Tube Wall

An analysis of the thermal and electric flow in an electrically heated tube is given in references 12 and 13. The basic assumptions of this analysis are negligible radial-voltage gradient and negligible axial-temperature gradient. For the case of a perfectly insulated outer wall, in which the thermal and electrical conductivities of the wall are linear functions of temperature, the equation for the temperature drop across a tube wall may be written as

$$t_{w,o} - t_{w,i} = \frac{JI^2 r_o^2 R_o}{k_o A_c^2}\left(\frac{R_{av}}{R_o}\right)^2 \frac{F}{1 + \sqrt{1 - AF}} \tag{A1}$$

where

$$F = \ln\left(\frac{1}{1 - S}\right) - \left(S - \frac{S^2}{2}\right) \tag{A2}$$

$$S = 1 - \frac{r_i}{r_o} \tag{A3}$$

$$\frac{R_{av}}{R_o} = \frac{S - \frac{S^2}{2}}{S - \frac{S^2}{2} + \frac{BS^3}{6}} \tag{A4}$$

$$A = \frac{JI^2 r_o^2 R_o}{A_c}\left(\frac{R_{av}}{R_o}\right)^2 \frac{\alpha_o}{k_o} \tag{A5}$$

$$B = \frac{JI^2 r_o^2 R_o}{A_c^2}\left(\frac{R_{av}}{R_o}\right)^2 \frac{\beta_o}{k_o} \tag{A6}$$

(All symbols are defined in appendix B.) For the conditions of this investigation,

$$\left(\frac{R_{av}}{R_o}\right)^2 \approx 1$$

Substituting the proper constants and dimensions in equation (A1) gives the tube-wall-temperature drop as

$$t_{w,o} - t_{w,i} = 2465I^2 \frac{R_o}{k_o}\left(\frac{0.0131}{1 + \sqrt{1 - 0.0131\ A}}\right) \tag{A7}$$

and

$$A = 2465I^2 \frac{R_o \alpha_o}{k_o} \tag{A8}$$

(R_o = (ohms)(sq ft)/ft; k_o = lb force/(sec)(^oR)). The heat flux at the tube inner wall is given by

$$q = \frac{JI^2R_o}{2\pi r_i A_c}\left(\frac{R_{av}}{R_o}\right) \tag{A9}$$

which for this investigation becomes

$$q = 5.22 \times 10^4\ R_o I^2 \tag{A10}$$

(R_o = (ohms)(sq ft)/ft).

The variation of the thermal conductivity of 303, 304, and 347 stainless steel with temperature is given in figure 18. The variation of the tube electrical resistance with temperature is given in figure 19. The computed tube-wall-temperature drop is given in figure 20 as a function of the heat flux and the tube-outer-wall temperature. For the conditions of the investigation, the wall-temperature drop ranges up to 20° R for the hydrogen conditions and up to 7° R for the nitrogen test conditions. These computed wall-temperature drops should be applied only for readings of thermocouples located in a region of negligible axial-temperature gradient.

Heat Flux

The local heat fluxes tabulated in table II were computed by

$$q = 282I^2R \qquad \text{(A11)}$$

which is the same as equation (A10) with a change in the constant resulting from using the resistance in ohms per inch of tube. The heat fluxes tabulated in table II include not only the critical heat flux but also the heat flux at the end of the tube, which was essentially constant over the entire tube length for the subcritical flux conditions (no transition).

APPENDIX B

SYMBOLS

A	factor defined in eq. (A5), dimensionless
A_c	tube-wall cross-sectional area, 4.5×10^{-4} sq ft
B	factor defined in eq. (A6), dimensionless
c_p	specific heat of liquid at constant pressure, Btu/(lb mass)($^{\circ}$R)
D	tube inside diameter, 0.04625 ft (0.555 in.)
F	factor defined in eq. (A2), dimensionless
G	test fluid mass velocity, lb mass/(hr)(sq ft)
h_{fg}	heat of vaporization, Btu/lb mass
I	heating current, amp
J	mechanical equivalent of heat, 778.3 ft-lb/Btu or 0.7376 lb force/(w)(sec)
k	thermal conductivity, Btu/(hr)(sq ft)($^{\circ}$R/ft) or lb force/(sec)($^{\circ}$R)
L	distance along tube axis measured from inlet station, in. (total length of tube, $16\frac{1}{8}$ in.)
p	pressure, lb/sq in. abs
Q	rate of heat flow, Btu/hr
q	heat flux, Btu/(hr)(sq ft)
R	tube electrical resistance, (ohms)(sq ft)/ft or ohms/in. of tube
r	radius measured from tube centerline, ft
S	factor defined in eq. (A3), dimensionless
t	temperature, $^{\circ}$R
w	fluid mass-flow rate, lb mass/hr
x	fluid quality or mass fraction of vapor defined in eq. (1), dimensionless

α coefficient of thermal conductivity as function of temperature, $1/^{o}R$

β coefficient of electrical resistivity as function of temperature, $1/^{o}R$

Subscripts:

av arithmetical average

cr critical (conditions at point of sudden rise of tube-wall temperature)

ex exit of tube

i inside surface of tube

in inlet of tube

o outside surface of tube

sat saturation condition

w wall of tube

REFERENCES

1. Zuber, Novak, and Fried, Erwin: Two-Phase Flow and Boiling Heat Transfer to Cryogenic Liquids. Paper 1709-61, Am. Rocket Soc., Inc., 1961.

2. DeBortoli, R. A., et al.: Forced-Convection Heat Transfer Burnout Studies for Water in Rectangular Channels and Round Tubes at Pressure Above 500 Psia. WAPD-188, Westinghouse Electric Corp., Oct. 1958.

3. Silvestri, Mario: Two-Phase (Steam and Water) Flow and Heat Transfer. Paper 39, 1961 Int. Heat Transfer Conf., Boulder (Colo.), Aug. 28-Sept. 1, 1961.

4. Lowdermilk, Warren H., Lanzo, Chester D., and Siegel, Byron L.: Investigation of Boiling Burnout and Flow Stability for Water Flowing in Tubes. NACA TN 4382, 1958.

5. Forster, K. E., and Greif, R.: Heat Transfer to a Boiling Liquid - Mechanism and Correlations. Jour. Heat Transfer, ser. C, vol. 81, no. 1, Feb. 1959, pp. 43-53.

6. Aladyev, I. T., et al.: Boiling Crisis in Tubes. Paper 28, 1961 Int. Heat Transfer Conf., Boulder (Colo.), Aug. 28-Sept. 1, 1961.

7. Wright, C. C., and Walters, H. H.: Single Tube Heat Transfer Tests, Gaseous and Liquid Hydrogen. TR 59-423, WADC, Aug. 1959.

8. Hendricks, R. C., Graham, R. W., Hsu, Y. Y., and Friedman, R.: Experimental Heat Transfer and Pressure Drop of Liquid Hydrogen Flowing Through a Heated Tube. NASA TN D-765, 1961.

9. Scott, Russell B.: Cryogenic Engineering. D. Van Nostrand Co., Inc., 1959.

10. Johnson, Victor J.: A Compendium of the Properties of Materials at Low Temperature (Phase 1). Pt. 1. Properties of Fluids. TR 60-56, WADD, July 1960.

11. Chang, Yan-Po, and Snyder, Nathan W.: Heat Transfer in Saturated Boiling. Preprint 104, ASME-AIChE, 1959.

12. Powell, Walter B.: Heat Transfer to Fluids in the Region of the Critical Temperature. Prog. Rep. 20-285, Jet Prop. Lab., C.I.T., Apr. 1, 1956.

13. Kreith, F., and Summerfield, M.: Investigation of Heat Transfer at High Heat-Flux Densities: Experimental Study with Water of Friction Drop and Forced Convection with and without Surface Boiling in Tubes. Prog. Rep. 4-68, Jet Prop. Lab., C.I.T., Apr. 2, 1948.

14. Zimmerman, James E.: Heat Conduction in Alloys and Semi-Conductors at Low Temperatures. D.Sc. Thesis, Carnegie Inst. Tech., 1951.

TABLE I. - THERMOCOUPLE LOCATIONS

Description	Station	Distance from inlet (measured positively downstream), in., for -	
		Runs 100 to 220	Runs 220 to 327
Tube outer wall	1	0.5	0.52
	2	1.5	1.5
	3	2.5	2.5
	4	3.5	3.41
	5	4.5	4.5
	6	5.5	5.41
	7	6.5	6.45
	8	7.5	7.53
	9	8.5	8.53
	10	9.5	9.53
	11	10.5	10.5
	12	11.5	11.48
	13	----	14.06
	14	----	14.56
	15	15.6	15.61
Copper bus Far	16	$-1\frac{7}{8}$	-1.81
Near	17	-7/8	-.88
Inlet section Near	18	-1/2	-0.5
Far	19	$-1\frac{1}{2}$	-1.44
Outlet section	20	17	17.22

TABLE II. -

(a) Hydrogen

Run	Pressure, p, atm	Inlet-fluid temperature, T_B, °R	Fluid-inlet temperature, °R	Fluid-exit temperature, °R	Inlet quality, $(x_i)_B$	Exit quality, $(x_{ex})_B$ or θ_B	Mass velocity, $\frac{lb}{(hr)(sq\ ft)}$	Heater element, no.	Critical heat flux, $\frac{Btu}{(hr)(sq\ ft)}$	Critical-boiling-length-to-diameter ratio	Critical quality	Tube-wall-exit temperature, °R: 1	2	3	4	5	6
100	41.0	5.10	156.0	156.0	---	.04	9,440	---	---	----	----	14	14	14	14	14	14
101	41.0	5.10	156.0	160.0	---	.06	9,440	---	---	----	----	14	14	14	14	14	14
102	43.0	46.6	92.0	117.0	---	.04	9,440	---	---	----	----	14	14	14	14	14	14
103	43.0	46.6	92.0	119.0	---	.06	9,440	---	---	----	----	14	14	14	14	14	14
104	42.0	47.0	92.0	92.0	---	0.0	14,160	---	---	----	----	14	14	14	14	14	14
105	40.0	44.4	92.0	92.0	---	0.0	18,880	---	---	----	----	14	14	14	14	14	14
106	40.0	44.4	46.0	96.0	---	0.0	9,440	532	------	----	----	100	220	260	300	356	316
107	40.0	44.4	56.0	121.0	---	0.0	9,440	532	------	----	----	92	240	304	440	432	332
108	40.0	44.4	77.0	107.0	---	0.0	9,440	532	------	----	----	100	272	328	360	436	428
114	40.0	44.4	46.2	46.0	0.1	.6	9,100	523	9,100	16.0	0.10	14	14	14	14	14	14
11	40.0	44.4	41.9	46.1	0.1	.3	18,200	492	18,200	14.2	.02	60	66	66	70	78	78
117	40.0	44.4	46.0	64.0	---	18.0	9,440	484	18,100	14.7	.68	14	14	14	14	14	14
118	41.0	44.4	43.7	46.8	0.4	-.2	9,440	536	12,700	14.8	.08	14	14	14	14	14	14
123	41.0	44.4	43.4	166.0	1.8	125.0	4,34[illegible]	591	13,400	4.0	.51	14	60	60	320	542	441
124	41.0	44.4	45.1	240.0	1.6	184.0	2,[illegible]	571	12,700	4.	.44	63	63	70	500	410	369
12[illegible]	41.0	44.4	44.7	203.0	1.0	175.	3,[illegible]	577	12,900	3.6	.23	60	64	290	580	404	344
120	40.0	44.4	45.2	222.0	1.0	150.	3,[illegible]	550	15,[illegible]	4.2	.52	60	64	170	533	576	442
12[illegible]	40.0	44.4	59.2	218.0	1.7	178.[illegible]	3,[illegible]	562	16,[illegible]	3.6	.76	56	60	310	437	466	365
128	40.0	44.4	41.0	45.0	0.0	.1	9,[illegible]	544	16,[illegible]	.20	.06	56	60	60	60	324	301
129	40.0	44.4	45.1	41.5	0.0	-.1	18,[illegible]	4.7	15,700	11.7	.33	60	60	60	60	60	58
130	40.0	44.4	42.3	41.7	0.0	.0	9,[illegible]	412	15,300	10.7	.02	60	60	60	60	60	60
131	40.0	44.4	44.1	44.4	1.6	-----	13,[illegible]	490	1[illegible],000	10.[illegible]	.21	60	60	66	66	70	70
132	40.0	44.4	44.1	42.7	1.3	.3	9,[illegible]	536	12,900	21.0	.76	60	60	70	62	60	60
133	40.0	44.4	44.4	70.0	.6	28.0	3,[illegible]	560	21,400	17.0	.82	60	66	66	66	66	66
134	40.0	44.4	44.3	45.8	1.1	.1	1,[illegible]	339	20,400	20.0	.63	60	66	66	66	66	66
135	40.0	44.4	44.[illegible]	103.0	1.3	57.0	2,[illegible]	362	25,000	10.5	.51	64	64	64	64	64	64
136	40.0	44.4	44.3	46.3	1.1	-.1	9,850	349	11,600	11.1	.19	68	68	68	68	68	68
137	40.0	44.4	44.3	48.0	1.1	.3	1,040	338	10,300	10.0	.46	66	66	66	66	66	66
138	40.0	44.4	44.4	140.0	1.6	103.0	4,040	571	12,400	4.[illegible]	.[illegible]	66	66	66	66	66	350
139	40.0	44.4	44.1	76.0	1.5	24.0	4,220	363	8,300	17.[illegible]	.77	66	66	66	66	66	66
14[illegible]	40.0	44.4	44.2	55.0	1.2	30.0	4,[illegible]	320	9,300	12.8	.51	64	64	64	64	64	64
144	40.0	36.8	36.8	36.8	---	.2	---- -	---	-------	----	----	48	47	47	47	47	47
145	40.0	43.2	46.0	46.7	1.8	-1.4	------	---	------	----	----	64	66	66	66	66	66
146	40.0	46.0	43.5	50.6	2.2	.1	10,900	488	18,700	----	----	284	464	516	504	484	478
147	40.0	46.0	46.7	69.0	2.1	38.2	12,600	439	22,400	----	----	227	366	456	434	450	446
148	40.0	46.0	45.0	130.0	2.5	91.2	5,690	488	21,400	----	----	208	462	518	525	515	515
149	40.0	46.0	47.1	90.0	.9	41.4	11,000	527	25,100	----	----	200	420	514	530	536	532
150	40.0	46.0	48.4	89.0	.2	33.4	10,750	510	24,300	----	----	244	362	494	500	492	490
151	40.0	46.0	48.4	140.0	3.1	94.1	4,030	484	21,100	----	----	552	577	600	598	578	575
152	40.0	46.0	42.9	97.0	----	51.5	13,100	436	20,100	----	----	242	464	537	536	508	498
153	41.0	46.0	43.4	160.0	2.8	120.0	7,230	419	20,400	----	----	200	424	478	472	482	504
167	41.0	46.[illegible]	38.5	38.0	0.2	107.[illegible]	2,420	442	14,600	----	----	341	397	492	529	504	503
162	30.0	41.5	40.0	41.5	2.5	.2	13,500	463	19,300	----	----	506	608	696	646	500	472
163	31.0	41.[illegible]	39.1	90.4	2.4	48.9	13,500	523	24,000	----	----	492	626	771	664	583	560
164	42.0	46.4	42.7	105.0	3.0	122.3	6,060	446	18,100	----	----	267	490	531	545	549	562
165	42.0	46.7	42.8	132.0	2.9	86.3	6,680	483	21,000	----	----	305	575	654	691	667	660
166	40.0	44.4	34.1	137.0	6.3	91.6	5,380	483	22,000	----	----	200	537	657	687	674	672
167	32.0	41.7	35.0	166.0	6.7	120.3	3,770	447	18,100	----	----	192	446	603	625	630	641
168	31.0	40.4	34.0	179.0	6.4	129.6	7,360	512	23,700	----	----	171	413	670	699	693	694
169	42.0	46.4	33.0	180.0	8.4	101.6	8,130	508	25,300	----	----	142	447	642	688	660	661
170	43.0	46.3	41.1	74.2	4.2	25.9	10,200	513	23,700	----	----	122	361	490	537	516	505
171	40.0	43.7	41.4	140.0	3.5	110.3	3,020	468	18,700	----	----	199	497	636	643	635	647
172	40.0	44.4	46.0	141.0	2.4	92.6	9,440	490	21,700	----	----	200	534	700	664	645	632
200	42.0	46.4	43.2	43.0	2.2	-2.4	18,000	---	------	----	----	45	45	45	45	45	45
203	40.0	41.3	41.0	43.0	.5	-.3	13,870	503	[a]11,600	[a]29+	[a]1.57	47	50	42	36	36	33
204	----	46.0	44.0	46.[illegible]	0	-.7	14,000	473	20,200	20.2	.07	60	58	54	50	46	42
205	40.1	8.4	41.4	44.8	1	-.1	12,000	457	18,[illegible]	19.[illegible]	.79	59	56	54	49	46	40
206	40.0	46.4	41.4	44.8	0	-.7	1,320	390	13,700	20.2	.17	52	54	56	50	46	45
207	41.0	46.5	42.4	44.7	0.8	-.6	9,530	468	19,000	8.0	.32	60	64	62	54	74	306
208	41.0	46.5	42.7	44.8	0.8	-.5	10,850	477	20,600	8.0	.31	60	64	64	60	70	389
210	41.0	46.1	42.4	44.8	0.7	-.3	11,890	518	24,300	8.[illegible]	.36	62	68	68	68	68	400
211	40.0	46.3	42.6	44.9	0.[illegible]	-.2	9,350	487	19,700	8.7	.43	62	64	64	64	64	323
212	40.0	46.3	43.0	43.8	1.8	-1.8	9,340	---	------	----	----	44	45	45	45	44	44
213	41.1	46.7	43.7	43.7	1.9	-1.9	10,020	---	------	----	----	43	45	45	45	44	45
214	40.0	46.4	42.3	44.8	0.6	-.9	9,240	200	[a]13,560	[a]29+	[a]1.21	48	50	50	50	50	50
215	40.0	46.3	42.1	44.6	5.2	-----	11,180	300	[a]6,[illegible]80	[a]29+	[a]1.46	50	52	52	52	52	54
216	50.0	45.8	----	-----	---	-----	7,015	448	19,200	8.0	----	50	56	54	50	216	342
217	50.7	46.0	44.3	45.3	1.6	-.6	10,450	448	19,200	14.0	.34	60	60	60	62	62	65
218	50.8	46.0	44.3	45.0	1.6	-.4	13,250	498	21,300	14.0	.40	58	60	62	66	66	70
25	40.0	44.4	42.7	44.4	2.8	-.5	11,430	537	14,400	26.2	.72	46	64	60	56	56	64
236	40.0	44.4	42.6	42.3	2.6	0	14,375	---	------	----	----	50	60	64	62	64	62
239	50.4	46.0	43.4	44.0	2.1	-1.6	11,500	396	14,300	27.0	.75	48	64	68	70	68	62
240	50.6	46.[illegible]	42.1	42.8	3.4	-2.7	11,650	405	14,900	25.2	.69	50	68	62	62	68	62
242	50.6	46.[illegible]	40.8	41.0	4.4	-4.5	11,[illegible]0	415	15,000	24.[illegible]	.68	46	66	60	68	68	66
242	40.0	44.4	43.1	43.1	2.3	-2.3	13,900	---	------	----	----	50	56	52	50	52	50
243	50.4	46.[illegible]	43.0	43.4	2.[illegible]	-2.1	11,[illegible]0	482	18,500	20.7	.72	48	62	60	---	70	66
244	40.[illegible]	44.6	42.3	42.5	2.3	-2.3	15,[illegible]60	---	------	----	----	50	56	52	50	54	52
246	50.5	43.4	-----	----	---	-----	4,100	261	8,200	28.0	----	42	60	52	52	50	54
250	50.[illegible]	46.[illegible]	41.6	43.1	3.9	-2.3	4,380	---	------	----	----	36	56	64	66	66	64
251	50.9	46.[illegible]	41.7	40.4	3.8	0	4,410	255	5,900	29.0	.63	56	66	60	46	54	50
252	51.0	46.8	41.7	42.4	3.9	-3.2	4,920	---	------	----	----	56	58	42	46	46	42

[a] Heat flux, length-to-diameter ratio, and quality are subcritical values and are taken as of tube-exit conditions.

EXPERIMENTAL DATA

(a) Hydrogen

TABLE II. - Concluded.

(a) Concluded. Hydrogen

Run	Pressure, lb/sq in. abs	Saturation temperature, °R	Fluid-inlet temperature, °R	Fluid-exit temperature, °R	Inlet subcooling, °R	Exit superheat, $t_{ex} - t_{sat}$, °R	Mass velocity, lb mass/(hr)(sq ft)	Heater current, amp	Critical heat flux, Btu/(hr)(sq ft)	Critical boiling-length-to-diameter ratio	Critical quality	Tube-outer-wall 1	2	3	4	5	6
253	[illegible]	45.7	42.3	[illegible]	3.4	-0.2	4,?20	263	6,250	25.7	0.77	39	75	60	50	54	52
254	[illegible]	45.6	42.4	[illegible]	3.2	-.2	4,500	266	6,500	26.0	.82	42	77	50	29	54	52
255	49.5	45.4	42.4	41.1	3.0	-.3	4,380	272	6,700	24.5	.81	42	77	50	42	54	52
256	51.0	45.6	43.1	45.3	2.5	-.3	4,450	313	8,850	20.?	.90	42	80	52	45	58	54
257	48.0	44.7	43.?	44.3	1.2	-.4	4,300	---	------	----	----	39	70	45	41	45	42
258	14.?	36.4	36.4	36.4	0	0	0	---	------	----	----	33	70	36	36	36	33
259	50.0	45.4	43.2	45.0	2.2	.1	4,100	291	7,700	21.5	.82	4	62	54	45	58	54
260	49.?	45.5	42.?	45.7	2.8	.4	4,170	312	8,800	20.5	.95	36	74	50	45	54	52
261	[illegible]	45.4	42.4	42.6	3.0	-2.8	4,035	---	------	----	----	42	70	47	45	47	41
262	49.9	[illegible]	43.4	[illegible]	2.0	.1	4,030	316	9,050	19.5	.9?	42	80	52	50	58	56
263	[illegible]	45.2	43.5	80.?	1.7	35.3	4,470	351	11,100	17.2	.90	4?	90	54	56	60	58
297	[illegible]	[illegible]	43.1	44.6	1.4	-.3	6,770	317	9,100	25.0	.75	50	88	56	58	62	58
298	47.7	45.0	43.6	44.9	1.4	-.1	6,520	316	9,050	20.2	.79	50	88	56	58	64	60
299	49.4	45.1	43.7	45.0	1.4	-.1	6,780	312	8,800	20.2	.76	50	89	56	58	62	60
300	46.1	44.7	43.7	44.8	1.0	.1	8,720	363	11,900	26.2	.81	50	90	56	----	68	62
301	2.5	45.6	43.0	45.?	2.6	-.3	4,440	263	6,300	26.2	.82	48	60	54	47	60	56
302	[illegible]	45.7	43.1	45.6	2.6	-.1	10,630	387	13,600	25.2	.73	48	85	60	58	68	64
303	[illegible]	45.?	43.1	45.4	2.4	-.1	12,620	416	15,700	26.2	.71	48	86	60	52	68	64
304	[illegible]	[illegible]	43.4	45.4	2.1	-.1	16,060	458	19,150	26.2	.65	48	86	64	50	74	70
305	[illegible]	45.4	43.6	----	1.8	-----	7,990	435	17,150	12.0	.56	48	83	66	64	75	74
306	[illegible]	45.1	43.1	----	2.0	-----	7,990	424	16,400	7.2	.30	70	79	72	72	385	443
307	48.?	45.4	43.6	45.4	1.8	0	5,740	373	12,600	18.2	.89	48	83	56	42	66	62
308	49.8	45.4	43.3	45.9	2.1	.5	5,510	382	13,200	15.7	.83	48	82	58	56	66	64
309	50.6	45.5	43.2	46.2	2.3	.7	6,060	389	13,750	14.0	.69	50	83	56	58	68	66
310	43.0	45.2	45.3	45.9	1.9	.7	8,330	440	17,650	13.5	.63	50	85	62	62	74	72
311	51.6	45.7	42.3	45.7	3.4	0	13,380	443	17,850	7.5	.17	45	79	62	54	269	330
312	53.0	45.9	44.9	46.0	1.0	.1	12,660	470	20,050	15.0	.53	47	93	62	----	74	72
313	50.3	45.6	41.2	45.5	4.4	-.1	16,200	415	15,650	5.0	.04	45	75	60	327	389	393
314	[illegible]	45.5	41.7	45.5	3.8	0	16,000	424	16,300	10.0	.17	47	75	60	54	66	100
315	50.9	45.6	41.7	45.5	3.9	-.1	16,660	425	16,350	12.5	.22	47	73	60	54	66	60
316	[illegible]	45.7	42.9	46.2	2.9	.5	11,200	444	17,900	13.5	.45	47	88	58	58	66	60
317	2.1	45.8	43.5	154.0	2.3	108.2	3,820	378	12,950	8.7	.64	42	75	52	52	58	277
318	50.8	45.6	43.8	45.6	1.8	0	6,190	397	14,300	8.5	.42	42	77	52	52	58	281
319	51.6	45.7	43.6	46.0	2.1	.3	9,310	419	15,900	8.5	.30	39	75	52	45	62	298
320	51.6	45.7	44.6	45.8	1.1	.1	10,920	430	16,750	8.5	.25	39	60	52	36	64	276
321	43.8	45.2	44.6	45.4	.6	.2	11,850	447	18,150	8.5	.29	36	79	54	47	70	292
322	51.5	45.7	45.6	-----	.1	-----	8,700	448	18,150	2.5	.12	45	97	268	305	374	459
323	50.0	45.4	45.5	45.5	-.1	.1	10,690	---	------	----	----	45	80	50	47	47	45
324	52.2	45.8	44.2	45.7	1.6	-.1	14,670	476	20,500	15.2	.46	42	75	58	52	66	64

(b) Nitrogen

Run	Pressure, lb/sq in. abs	Saturation temperature, °R	Fluid-inlet temperature, °R	Fluid-exit temperature, °R	Inlet subcooling, °R	Exit superheat, $t_{ex} - t_{sat}$, °R	Mass velocity, lb mass/(hr)(sq ft)	Heater current, amp	Critical heat flux, Btu/(hr)(sq ft)	Critical boiling-length-to-diameter ratio	Critical quality	Tube-outer-wall 1	2	3	4	5	6
264	55.3	163.2	162.0	165.0	1.2	1.8	17,030	297	8,870	21.5	0.57	165	198	170	175	173	171
265	54.1	162.8	159.0	164.0	4.8	1.2	24,030	304	9,250	25.0	.46	163	195	169	171	172	171
266	54.6	163.0	160.0	165.0	3.0	2.0	24,300	322	10,400	23.7	.50	164	197	170	179	174	172
267	50.2	161.4	158.0	161.0	3.4	-.4	36,000	345	11,900	25.0	.38	162	195	169	167	171	171
268	48.5	160.7	157.5	160.5	3.2	-.2	30,400	323	10,400	23.5	.39	160	194	167	171	170	170
269	54.3	163.0	160.0	163.0	3.0	0	29,800	313	9,800	21.5	.35	165	197	170	174	173	172
270	56.0	163.5	161.5	163.5	2.0	0	42,300	355	12,600	24.2	.36	165	197	170	165	175	173
271	50.2	161.4	157.0	162.0	4.4	.6	31,000	325	10,600	24.0	.39	161	193	167	171	171	170
272	49.8	161.2	157.0	162.0	4.2	.8	30,800	326	10,650	29+	.49	161	193	166	173	171	170
273	50.1	161.3	157.0	160.5	4.3	-.8	15,700	309	[a]9,550	[a]29+	[a].87	163	195	167	169	170	169
274	49.8	161.2	158.0	160.5	3.2	-.7	15,100	314	[a]9,850	[a]25+	[a].95	161	194	165	168	169	168
275	55.3	163.2	157.5	163.0	5.7	-.2	19,750	301	9,050	22.0	.48	162	194	167	163	171	170
276	50.4	161.4	158.0	160.5	3.4	-.9	16,250	316	[a]10,000	[a]29+	[a].89	163	195	167	165	171	170
277	52.5	162.2	159.0	162.0	3.2	-.2	22,850	302	9,150	22.5	.44	164	196	169	167	172	171
278	52.0	162.0	159.0	162.0	3.0	0	27,200	316	10,000	24.0	.43	164	197	168	175	171	170
279	50.0	161.3	157.0	161.0	4.3	-.3	25,100	352	[a]12,350	[a]29+	[a].70	159	194	165	171	170	169
280	50.0	161.3	157.0	162.0	4.3	.7	24,400	367	13,300	29.0	.78	159	194	165	176	170	169
281	50.5	161.4	157.0	161.0	4.4	-.4	24,100	361	[a]13,000	[a]29+	[a].77	159	194	166	165	171	170
282	50.6	161.5	157.5	161.0	4.0	-.5	23,600	371	13,800	29.0	.84	160	195	165	165	171	170
283	50.3	161.4	156.0	162.0	3.4	.6	24,500	308	9,500	23.5	.44	160	191	165	167	168	167
284	51.0	161.7	157.5	161.5	4.2	-.2	31,100	408	[a]16,700	[a]29+	[a].77	160	197	167	171	172	171
285	54.4	163.0	159.0	163.0	4.0	0	31,500	400	16,000	29.0	.73	160	198	169	171	173	172
286	55.0	163.2	159.0	163.0	4.2	-.2	31,700	406	16,500	29.0	.75	161	200	170	178	174	173
287	55.0	163.2	159.0	163.0	4.2	-.2	31,100	413	[a]17,100	[a]29+	[a].79	160	200	170	166	173	172
289	50.2	161.4	157.0	160.0	4.4	-.4	41,900	453	[a]20,550	[a]29+	[a].70	160	201	170	176	175	172
290	50.5	161.4	156.5	160.5	4.9	-.9	40,600	453	20,550	29.0	.72	161	202	170	168	174	173
291	49.2	160.6	157.0	161.0	3.8	.2	41,700	346	11,950	24.0	.40	160	194	167	171	171	170
292	50.8	161.5	158.0	161.0	3.5	-.5	56,300	489	[a]24,000	[a]29+	[a].61	161	205	171	172	177	176
293	49.6	161.2	157.0	161.0	4.2	-.2	32,400	154	[a]2,350	[a]29+	[a].08	159	167	162	167	163	162
294	49.5	161.1	157.0	161.0	4.1	-.1	31,400	208	[a]4,300	[a]29+	[a].18	160	188	163	167	164	163
295	49.7	161.1	157.0	161.0	4.1	-.1	31,200	255	[a]6,500	[a]29+	[a].28	160	189	163	169	167	164
296	49.6	161.1	157.0	161.0	4.1	-.1	31,700	323	[a]10,400	[a]29+	[a].46	160	192	165	170	168	167
325	47.5	160.2	158.5	159.7	1.7	-.5	31,900	---	------	----	----	160	184	159	163	160	160
326	49.9	161.3	159.0	161.0	2.3	-.3	28,000	325	10,550	17.0	.31	161	197	166	166	171	167
327	51.3	161.8	159.7	162.0	2.1	.2	24,400	384	14,700	3.0	.08	164	294	833	1132	1320	1455
272a	50.0	161.2	158.2	-----	3.0	-----	30,800	410	17,000	29.0	.80	---	---	---	----	----	----
272b	50.0	161.2	158.2	-----	3.0	-----	37,500	459	21,300	29.0	.82	---	---	---	----	----	----
276a	50.4	161.4	158.0	161+	3.4	0	15,500	315	10,000	29.0	.93	---	---	---	----	----	----
292a	51.0	161.7	158.0	162.0	3.7	.3	53,800	503	25,800	29.0	.69	---	---	---	----	----	----
325a	50.5	161.5	156.5	161+	3.0	0	24,000	367	13,500	29.0	.82	---	---	---	----	----	----
326a	49.9	161.0	159.0	161.0	2.0	0	30,400	390	15,300	29.0	.73	---	---	---	----	----	----

[a]Heat flux, length-to-diameter ratio, and quality are subcritical values and are taken as of tube-exit conditions.

EXPERIMENTAL DATA

(a) Concluded. Hydrogen

temperature, °R, at station - 7	8	9	10	11	12	13	14	15	Copper bus temperature, °R: Far	Copper bus temperature, °R: Near	Inlet plenum wall temperature, °R: Near	Inlet plenum wall temperature, °R: Far	Exit plenum wall temperature, °R	Amplitude of tube wall temperature fluctuations: ±°R	Amplitude of tube wall temperature fluctuations: At station -	Remarks
50	50	50	94	58	52	65	100	171	272	316	52	52	54	30 36	13 14	
52	52	52	90	58	52	62	80	122	274	318	54	54	54	8 20	13 14	Transition; maximum-critical-flux value
52	52	52	80	56	52	52	108	119	274	318	54	52	56	3	15	
52	54	54	91	66	179	379	392	375	280	325	294	242	183	14	12	
42	42	42	504	47	42	39	39	42	263	307	42	42	45	---	--	No-heat run; control valves in same position as in run 256
33	33	33	505	36	33	29	29	33	262	308	33	29	36	---	--	Vented system to atmosphere
56	54	54	90	64	58	328	341	329	281	326	249	192	148	2	14	Transition; maximum-critical-flux value
52	52	52	108	62	172	402	413	397	281	326	315	268	285	4	12	
45	45	45	----	50	45	42	42	42	266	311	45	45	45	---	--	No-heat run; control valves in same position as in run 260
54	56	56	566	103	260	428	437	421	287	333	346	306	211	23	11	Transition; maximum-critical-flux value
56	56	109	549	389	443	592	605	564	293	339	489	455	272	21	9	Transition; maximum-critical-flux value; difficult to stabilize because of flow oscillations
58	56	56	60	68	60	124	235	186	287	332	62	60	60	49 17	13 14	
58	58	58	62	68	62	91	167	188	287	331	62	60	60	26 12	13 14	
58	58	58	62	70	62	62	66	155	287	332	62	60	60	6	4	
60	60	60	62	72	64	64	70	230	294	338	66	64	69	---	--	Transition; maximum-critical-flux value
56	54	54	56	64	56	60	83	105	283	307	60	58	60	17 38	14 15	
62	62	62	64	72	66	68	72	108	296	343	68	66	64	34	15	
64	62	64	66	72	66	70	72	236	301	347	70	68	100	5	15	
68	68	66	70	77	72	74	60	203	307	354	74	72	100	6	15	
75	361	423	461	492	509	568	571	538	303	350	529	519	270	---	--	Transition; conditions impossible to stabilize; temperatures kept changing
451	457	466	470	480	489	511	512	489	302	349	490	488	241	---	--	
60	60	60	62	260	344	511	522	498	296	343	439	401	243	---	--	
60	62	62	294	375	426	566	576	544	297	344	492	460	268	1	14	Transition; maximum-critical-flux value
64	64	305	375	420	451	524	554	521	299	346	491	467	266	---	--	
72	132	387	439	471	492	556	564	535	307	354	525	514	269	---	--	Transition
424	416	406	405	409	410	424	429	409	303	359	411	409	207	---	--	Transition; maximum-critical-flux value
68	68	239	375	413	434	504	511	487	314	361	465	410	231	---	--	
373	361	357	351	353	348	347	352	332	300	335	315	310	140	---	--	Transition
365	380	375	372	370	366	362	368	349	301	347	356	359	148	---	--	
58	326	351	355	361	361	361	362	346	300	346	357	357	143	---	--	
56	104	352	367	411	426	468	472	450	302	349	440	439	222	---	--	
360	407	447	487	523	553	665	665	635	294	340	609	583	320	8	13	Transition; maximum-critical-flux value
359	366	415	430	451	463	517	520	433	295	342	487	476	260	---	--	
377	392	404	409	418	421	444	447	424	299	346	427	425	212	---	--	Transition
365	393	406	412	418	420	441	444	419	300	348	423	416	204	13	4	
392	422	434	433	441	442	459	463	436	303	350	431	430	187	---	--	
553	618	626	596	575	561	573	577	540	319	364	[illegible]	561	270	4	12	Transition; took 3 hr to obtain equilibrium; at first had increasing temperature profile; later profile peaked
45	45	48	45	50	45	42	42	45	276	321	47	47	45	---	--	No-heat run to check wall thermocouples
54	50	101	473	420	441	479	482	415	309	357	462	454	213	---	--	Transition; similar behavior as in run 522

(b) Nitrogen

7	8	9	10	11	12	13	14	15	Copper bus Far	Copper bus Near	Inlet plenum Near	Inlet plenum Far	Exit plenum	±°R	At station -	Remarks
171	173	172	173	178	175	865	890	650	346	384	549	179	175	---	--	
171	172	171	172	175	173	451	618	524	348	380	175	174	174	3	15	
172	173	172	173	176	174	705	785	635	345	383	177	175	175	3	15	
171	172	171	171	174	172	552	725	629	345	383	173	173	173	2	15	
170	170	170	170	173	171	805	650	660	341	377	173	171	171	4	13	Transition; on all these runs either power was decreased or flow rate increased as desired transition condition was approached to prevent overheating and instability
172	174	173	175	179	176	805	830	626	340	378	----	179	175	---	--	
173	174	173	174	177	175	675	800	660	346	363	175	175	173	5	15	
170	171	170	171	173	171	725	805	639	337	373	173	173	172	---	--	
170	171	170	171	173	171	173	172	172	336	371	172	171	171	---	--	
169	170	170	170	171	171	172	172	172	343	380	171	171	170	---	--	No transition; close to maximum-critical-flux value
168	169	168	168	170	169	171	170	170	343	380	170	170	168	---	--	No transition
170	171	170	171	174	172	760	795	590	340	377	174	173	172	---	--	Transition; close to maximum-critical-flux value
170	170	170	170	172	171	173	173	172	345	382	171	171	170	---	--	No transition; close to maximum-critical-flux value
171	171	171	171	175	172	721	764	601	343	380	175	173	172	3	15	Transition
170	171	170	171	173	172	660	761	619	346	383	174	173	172	2	15	
168	169	168	169	171	170	171	171	171	342	379	171	171	170	---	--	No transition
168	169	168	169	171	170	805	961	730	343	380	171	171	170	12 11	13 14	Transition; maximum-critical-flux value
169	169	168	170	171	170	171	171	171	344	381	171	171	170	---	--	No transition
169	170	169	170	171	170	172	172	172	346	383	171	172	170	---	--	Transition; maximum-critical-flux value
167	168	167	168	170	169	660	736	598	337	373	170	170	169	1	15	Transition
170	171	171	171	172	171	173	174	172	351	390	172	172	171	---	--	No transition; close to maximum-critical-flux value
171	172	171	172	175	173	175	176	174	350	390	173	173	172	---	--	Transition; maximum-critical-flux value
172	173	172	173	175	174	175	176	175	352	391	174	174	171	---	--	
171	172	172	173	174	173	175	176	174	353	392	174	174	171	3	4	No transition; close to maximum-critical-flux value
171	172	171	172	176	173	175	176	174	361	392	174	174	171	---	--	No transition
172	173	172	173	176	174	175	177	175	362	404	174	174	171	---	--	Transition; maximum-critical-flux value
169	170	169	170	172	171	690	793	642	343	381	173	172	172	4	15	Transition
174	175	174	175	179	176	177	179	175	369	411	176	177	171	---	--	No transition; close to maximum-critical-flux value
163	163	163	163	164	163	164	164	165	325	361	163	163	166	---	--	
164	164	163	164	165	165	167	166	167	326	365	166	165	167	---	--	No transition
165	166	165	167	168	167	169	168	168	333	370	167	167	168	---	--	
167	167	167	169	170	169	171	171	170	342	380	170	170	170	---	--	
160	160	160	160	160	160	159	159	160	318	356	160	160	160	---	--	No-heat run; thermocouple check
168	169	166	386	776	900	1175	1170	890	349	385	1055	978	159	3	10	Transition; difficult to control
1530	1560	1680	1730	1760	1755	1740	1770	1600	470	404	1801	1915	705	[illegible]	6	
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	All these data taken while attempting to obtain maximum critical flux for transition at end of tube; data represent last readings taken before final power or flow adjustment, which caused instability and gave transition upstream at heat-flux values considered to be less than maximum critical flux
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	
----	----	----	----	----	----	----	----	----	---	---	----	----	---	---	--	



Figure 1. - Schematic drawing of cryogenic boiling-heat-transfer apparatus.



Figure 2. - Details of test section, inlet, and exit.



(a) Mass velocity, approximately 12,000 pounds per hour per square foot.

Figure 3. - Tube-outer-wall temperature profiles for constant mass velocity and varying heat flux and location of transition. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(b) Mass velocity, approximately 4500 pounds per hour per square foot.

Figure 3. - Concluded. Tube-outer-wall temperature profiles for constant mass velocity and varying heat flux and location of transition. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 20 R.



Figure 4. - Tube-outer-wall temperature profiles for flow of cool hydrogen gas through heated tube at several pressure, temperature, flow-rate, and heating-rate conditions.



(a) Critical-boiling-length-to-diameter ratio, approximately 15.

Figure 5. - Tube-outer-wall temperature profiles for constant transition location and varying heat flux and mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(b) Critical-boiling-length-to-diameter ratio, approximately 8.5.

Figure 5. - Concluded. Tube-outer-wall temperature profiles for constant transition location and varying heat flux and mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 20° R.



(a) Critical-boiling-length-to-diameter ratio, approximately 26.

Figure 6. - Variation of critical heat flux with mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(b) Critical-boiling-length-to-diameter ratio, approximately 20.

Figure 6. - Continued. Variation of critical heat flux with mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(c) Critical-boiling-length-to-diameter ratio, approximately 15.

Figure 6. - Continued. Variation of critical heat flux with mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(d) Critical-boiling-length-to-diameter ratio, approximately 8.5.

Figure 6. - Concluded. Variation of critical heat flux with mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



Figure 7. - Comparison of tube-outer-wall temperature profiles for maximum and submaximum critical-heat-flux conditions. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



Figure 8. - Comparison of tube-outer-wall temperature profiles for submaximum critical-heat-flux conditions at various heat fluxes and constant mass velocity. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



(a) Test-section pressure, approximately 50 pounds per square inch absolute.

Figure 9. - Tube-outer-wall temperature profiles for liquid hydrogen with wall temperature rise at tube inlet.



(b) Test-section pressure, approximately 70 pounds per square inch absolute.

Figure 9. - Concluded. Tube-outer-wall temperature profiles for liquid hydrogen with wall temperature rise at tube inlet.



Figure 10. - Variation of maximum critical heat flux with mass velocity at various critical-boiling-length-to-diameter ratios. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



Figure 11. - Variation of maximum critical heat flux with critical-boiling-length-to-diameter ratio at various mass velocities. Liquid hydrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



Figure 12. - Variation of critical heat flux with mass velocity at critical-boiling-length-to-diameter ratio of 29. Liquid nitrogen; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 4° R.



Figure 13. - Comparison of maximum critical boiling heat flux with submaximum critical boiling heat flux. Liquid nitrogen; test-section pressure, 48 to 53 pounds per square inch absolute; inlet subcooling, 19 to 60 R.



Figure 14. - Comparison of maximum critical heat flux for cryogenic liquids with water correlation of reference 4.



Figure 15. - Comparison of maximum critical heat flux for cryogenic liquids with water in terms of revised geometric parameters.



Figure 16. - Maximum critical heat flux as function of flow and length parameter. Boiling liquid hydrogen; tube inside diameter, 0.555 inch; test-section pressure, approximately 50 pounds per square inch absolute; average inlet subcooling, 2° R.



Figure 17. - Nucleate heat flux as function of wall superheat. Liquid nitrogen; test-section pressure, 48 to 56 pounds per square inch absolute; inlet subcooling, 3° to 5° R; length-to-diameter ratio, 29.



Figure 14. - Variation of thermal conductivity of 303, 304, and 347 stainless steel with temperature.



Figure 19. - Variation of tube electrical resistance with temperature. Tube of 304 stainless steel; outside diameter, 0.625 inch; inside diameter, 0.555 inch.



(a) Hydrogen test conditions.

Figure 20. - Temperature drop across tube wall as function of heat flux and tube-outer-wall temperature. Negligible axial temperature gradient; tube of 304 stainless steel; inside diameter, 0.555 inch; wall thickness, 0.035 inch.



(b) Nitrogen test conditions.

Figure 20. - Concluded. Temperature drop across tube wall as function of heat flux and tube-outer-wall temperature. Negligible axial temperature gradient; tube of 304 stainless steel; inside diameter, 0.555 inch; wall thickness, 0.035 inch.